

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/041211 A2

(51) International Patent Classification⁷: **H01B**

(21) International Application Number:
PCT/IL2004/000967

(22) International Filing Date: 24 October 2004 (24.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/513,998 27 October 2003 (27.10.2003) US

(71) Applicant (for all designated States except US): **TECHNION RESEARCH & DEVELOPMENT FOUNDATION LTD.** [IL/IL]; Att: Ami Lowenstein, Senate House, Technion City, 32000 Haifa (IL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SHOHAM, Moshe** [IL/IL]; Hoshaya, M.P. Hamovil, 17915 Hoshaya (IL).

(74) Agent: **SECEMSKI, Dr. Ephraim**; P.O. Box 4500, 91044 Jerusalem (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TWISTING WIRE ACTUATOR



(57) Abstract: A twisted wire actuator, whereby the shortening of the length of a wire or a bundle of wires, as it is twisted, is used to control the motion of an actuated element, achieving sub-micron motion resolution. The control can be performed robotically. The high resolution can be achieved without the use of gears, sliders, or high precision lead screws, thus enabling a simplified actuation system and eliminating sources of friction. The use of wires operating in opposing directions and having oppositely directed rotations significantly reduces the non-linearity effect inherent in twisted wire actuation, resulting in a system having a good level of motion linearity as a function of control input impulse. The use of multiple twisted wires attached to the actuated element at different angles, enables the implementation of robotic systems with multiple degrees of freedom. Several experimental actuators verify these results.

WO 2005/041211 A2